



	Premium Model DF.0.DEH	Model SG.0.DTS
Beschikbare modellen / Available models	0.25 - 2 ton / 400V	0.25 - 15 ton / 400V
Hijssnelheid / Lifting speed	0.250 ton	8/2 m/min
	0.500 ton	8/2 m/min
	1.000 ton	8/2 m/min
	2.000 ton	4/1 m/min
Netto gewicht / Net weight	0.250 ton	22 kg
	0.500 ton	33 kg
	1.000 ton	53 kg
	2.000 ton	58 kg

Vergelijking van behuizing afmetingen /
Comparison of body dimensions

0.25 ton



0.5 ton



1 - 2 ton



Behuizing bescherming / Housing protection	IP 55
Classificatie / Classification	M5/2m (ISO/FEM)
Inschakelduur / Duty cycle	40%
Stuurspanning / Control voltage	24 V
Overlastbeveiliging / Overload protection	Slipkoppeling + digitale beveiliging / Slip clutch + digital protection
Eindschakelaar / Limit switch	Hoogste en laagste microscharlaar / Upper and lower micro switch
Thermische bescherming / Thermal protection	Warmtesensor / Heat sensor
Hijsketting / Load chain	
Besturingssysteem / Control system	SIEMENS